R226 MIFI Wireless dongle device



Step 1

Insert your SIM

Remove back cover

Insert SIM





Open the menu of the device

Press the Menu button (1)

Highlight the Wi-Fi Band option (press Menu/Next) twice and press Power/ OK (button 2).









In the Wi-Fi Band option select the 2.4GHz and press Power/OK button

Menu /Next
Power / OK





Connect to Wi-Fi

Turn on the Wi-Fi on your laptop

For Lenovo: Press the **FN** button of the laptop keyboard + **F8** (icon of the signal tower)



For HP: Press the Wi-Fi button on the top right hand side corner (when it is on it glows white – when the Wi-Fi is off it glows orange)



Right click on the network connection icon on the taskbar and select to connect to your Mi-Fi

The Mi-Fi SSID (network connection name) will be on the card in the box of the Mi-Fi device



You will be promted for a password. You will find the password on the same card in the box of the device

Connect to a Netv	vork		×
Type the netwo	rk security key		
Security key:			
	Hide characters		
		ОК	Cancel

Once you have connected to the Wi-Fi you need to connect to the HSE VPN network through CheckPoint security software.

If the software icon (**yellow padlock**) is not right from the date and time (default location is right hand side bottom corner of the screen), click on the **show hidden icons** arrow (1).

Right click (2) on the yellow padlock icon of the CheckPoint software and select "Connect to.." (3)



Enter your VPN login details and click "Connect"

Check Point Endpoint Security			
Endpoint S	Security [.]	Check Point SOFTWARE TECHNOLOGIES LTD	
Site:	137.191.241.9		
Authentication Username:	a-user		
Password:			
Connect	Cancel Help		



lf you are unsure

<u>on how to use</u>

this guide please

call national

helpdesk at

<u>0818300300</u>